

TUSCANY BIANCO PLUS

Glazed Ceramic Tile

SURFACE	Satin
SIZE	32 x 57 cm / 13" x 22"
THICKNESS	7.2 mm / 0.28 in
COVERAGE / CARTON	2.03 m ² / 21.85 ft ²



PERFORMANCE & TECHNICAL CHARACTERISTICS

PROPERTY	TECHNICAL VALUE	REFERENCE / NOTES
Classification Group	BI Ib	Water absorption: 6% < Ev <= 10%. ABNT NBR ISO 13006, Annex K.
Coefficient of Friction	Class I < 0.4	Satisfactory for normal installations - dry and wet areas. NBR 16919.
Suggested Use	LB	Suitable for indoor residential areas except balconies and garages without direct access to the street, as well as for LA areas.
Breaking Strength	>= 500 N	For thickness < 7.5 mm. ABNT NBR ISO 13006 / Ceramica Carmelo Fior.
Modulus of Rupture	Average >= 18 N/mm ²	Individual >= 16 N/mm ² .
Stain Resistance	>= Class 3	ABNT NBR ISO 13006 / Ceramica Carmelo Fior.

PRODUCT APPLICATION

Suitable for indoor residential areas except balconies and garages without direct access to the street, as well as for LA areas.

Technical values reproduced from the manufacturer's technical specification for Tuscany Bianco Plus. Product appearance may vary slightly due to shade, production batch, screen, and printing conditions.