

TUSCANY BIANCO PLUS

Glazed Ceramic Tile

SURFACE	Matte
SIZE	45 x 45 cm / 18" x 18"
THICKNESS	7 mm / 0.27 in
COVERAGE / CARTON	2 m ² / 21.53 ft ²



PERFORMANCE & TECHNICAL CHARACTERISTICS

PROPERTY	TECHNICAL VALUE	REFERENCE / NOTES
Classification Group	BI Ib	Water absorption: 6% < Ev <= 10%. ABNT NBR ISO 13006, Annex K.
Coefficient of Friction	Class I < 0.4	Suitable for normal installations - dry and wet areas. NBR 16919.
Suggested Use	LB	Residential indoor. Not indicated for balconies, garages, or barbecue areas.
Breaking Strength	>= 500 N	For thickness < 7.5 mm. ABNT NBR ISO 13006 / Ceramica Carmelo Fior.
Modulus of Rupture	Average >= 18 N/mm ²	Individual >= 16 N/mm ² .
Stain Resistance	>= Class 3	ABNT NBR ISO 13006 / Ceramica Carmelo Fior.

PRODUCT APPLICATION

Residential indoor: indicated for indoor residential environments, without exposure to excessive moisture or significant thermal variations. Not indicated for balconies, garages, or barbecue areas.

Technical values reproduced from the manufacturer's technical specification for Tuscany Bianco Plus. Product appearance may vary slightly due to shade, production batch, screen, and printing conditions.