

UDDO OSAKA PLUS

Glazed Ceramic Tile

SURFACE	Satin
SIZE	20 x 60 cm / 8" x 24"
THICKNESS	8.5 mm / 0.33 in
COVERAGE / CARTON	1.70 m ² / 18.30 ft ²



PERFORMANCE & TECHNICAL CHARACTERISTICS

PROPERTY	TECHNICAL VALUE	REFERENCE / NOTES
Water Absorption Group	BI Ib	6% < Ev <= 10%. ABNT NBR ISO 13006, Annex K.
Coefficient of Friction	Class I < 0.4	Satisfactory for normal installations - dry and wet areas.
Suggested Use	LC	Residential areas with direct street access and internal commercial areas; also suitable for LB areas.
Shade Variation	V3 - Moderate	Intentional variation in color/design. Variation of faces: 8.
Breaking Strength	>= 800 N	Applicable to thickness >= 7.5 mm.
Modulus of Rupture	Average >= 18 N/mm ²	Individual >= 16 N/mm ² .
Stain Resistance	>= Class 3	Water stain resistance: Yes.
Chemical Resistance	Minimum GLB	Household cleaning products, pool salts, alkalies and low-concentration acids.

PRODUCT DETAILS

For floor and wall use. Relief: Yes. Edge: Bold. Pieces per carton: 14. Recommended grout joint: 3 mm / 0.12 in. Fire reaction / combustibility: Class I (non-combustible ceramic material).

Technical values reproduced from the manufacturer's technical specification for Uddo Osaka Plus (internal code 19301). Product appearance may vary due to the declared V3 shade variation and digital face variation.