

UDDO TOKYO PLUS

Glazed Ceramic Tile

SURFACE	Satin
SIZE	20 x 60 cm / 8" x 24"
THICKNESS	8.5 mm / 0.33 in
COVERAGE / CARTON	1.70 m ² / 18.30 ft ²



PERFORMANCE & TECHNICAL CHARACTERISTICS

PROPERTY	TECHNICAL VALUE	REFERENCE / NOTES
Water Absorption Group	BI Ib	6% < Ev <= 10%. ABNT NBR ISO 13006, Annex K.
Coefficient of Friction	Class I < 0.4	Satisfactory for normal installations - dry and wet areas.
Suggested Use	LB	Indoor residential areas except balconies and garages without direct access to the street; also suitable for LA areas.
Shade Variation	V3 - Moderate	Intentional variation in color/design. Number of faces: 8.
Breaking Strength	>= 800 N	Applicable to thickness >= 7.5 mm.
Modulus of Rupture	>= 18 N/mm ²	For thickness >= 7.5 mm.
Stain Resistance	>= Class 3	Greater watermark resistance: Yes.
Chemical Resistance	Minimum GLB	Household cleaning products, pool salts, alkalis and low-concentration acids.

PRODUCT DETAILS

For floor and wall use. Edge: Flat. Pieces per carton: 14. Minimum laying joint: 3 mm. Fire reaction / combustibility: Class I (non-combustible ceramic material).

Technical values reproduced from the manufacturer's technical specification for Uddo Tokyo Plus (internal code 19302). Product appearance may vary due to the declared V3 shade variation and digital face variation.